



Studio Monitor - Tarif TTC 2022

PRODUIT	Prix € / pièce
Line-Master active 3.5 - ways-cylindrical wave guider with 2 x8', 4 x 6.5", 1" on driver cylindrical wave guide driver, 750 RMS power, 20 Hz – 24000 Hz	28.560,00
A Line	
ADM15 FIRTEC(TM) controlled, digital signal processing, 3 way active main-monitor 1"driver, 3" midrange calotte, 15" high-performance woofer remotable, 1000 W, 27 Bit ADC, AES3-Input	7.021,00
A100 (cherry / black) 2-way active midfield reference studio speaker FIRTEC(TM) controlled digital signal processing 1.2 " tweeter, 8" woofer remotable, 70 + 170 W	1.285,20
A200 mk2 (left / right) 3-way active midfield reference studio speaker FIRTEC(TM) controlled digital signal processing 1"driver, 3"midrange calotte, 10"woofer remotable, 650 W, ADC, 192 KHz - 24 Bit-AES3-Input	2.612,05
A500 (left / right) 3-way active midfield reference studio speaker FIRTEC(TM) controlled digital signal processing 1"horn,3 "midrange dome, 2 x 10 "woofer remotable, 650 W, ADC, 192 KHz - 24 Bit-AES3-Input	6.991,25
B300 Subwoofer Extension for A300 / A200 Digital signal processing-Controller 2 pcs. 10" woofer remotable, 500 W	3.997,21
Mainstack Main monitor system: A500 + B300 Digital signal processing-Controller 1"horn,3"midrange dome, 4 x 10"woofer > 1000 W	9.996,00

Coaxial Reference Line

C5-Reference (cherry / black)	940,10
2-way active coax nearfield studio speaker, FIRTEC-DSP controlled 1.45" neodyne tweeter, 6" sub, 80 + 175 W, adj. treble, bass, volume XLR bal. input, +4 dBV, 48 – 24.000 Hz (+/- 3 dB)	

C8-Reference (cherry / black)	1.154,30
2-way active coax near / midfield studio speaker, FIRTEC-DSP controlled 1.45" neodyne tweeter, 8" carboncone, 80 + 175 W, adj. treble, bass, volume XLR bal. input, +4 dBV, 38 – 24.000 Hz (+/- 3 dB)	

C88-Reference (cherry / black - left / right)	1.541,05
3-way active coax midfield studio speaker, FIRTEC-DSP controlled coax 1.45" neodyne tweeter - 8" carboncone, 8" carboncone bass 80 W + 250 W + 250 W, adj. treble, bass, volume XLR bal. input, +4 dBV, 32 – 24.000 Hz (+/- 3 dB)	

B88-Reference (cherry / black)	1.541,05
DSP-controlled subwoofer with double 8" bass driver 250W + 250W adj. Volume, delay XLR bal. input, +4 dBV, 28 – 80Hz (+/- 3 dB), highpassed XLR – stereo-outputs	

C100-Coax	2.378,81
2-way active coax midfield studio speaker / Coax 1" highrangedriver - 10" bassdriver 250 W / 250 W analog amplifier with digital signal processing remotable, ADC, 192 KHz – 24 Bit-AES3-Input	

C120-Coax	4.040,05
2-way active coax midfield studio speaker / Coax 1" highrangedriver - 12" bassdriver 250 W / 250 W analog amplifier with digital signal	

CB120-CX-Bass-Extension	3.268,93
self powerd 12"-speaker, monocrossover and highpass out for satellite	

CB150-CX-Bass-Extension	3.564,05
self powerd 15"-speaker, monocrossover and highpass out for satellite	

CX-Stand	1.213,80
stand pour CX-System	

Accessories

KSD-RC Remote Control	999,60
Telecommande pour KSD	

KSD-VC Volume Control	221,34
Volume Controller for KSD	

DDC- Digital-Digital-Converter	499,80
SPDIF-Cinch, Optical, AES-IN → 2 x AES-XLR-OUT Reclocker, Samplerate Converter	