


**MANGER**  
PRÄZISION IN SCHALL

Tarif Public Euro TTC 10/2022

Image	Ref.	Description	Finition	Prix/pièce	
	p1	Type	Passive 2-Way Floorstanding Speaker	RAL or NCS colors (satin finish)	6.400,00
		Impedance	4 Ohms	Standard veneers (satin finish)	6.700,00
		Frequency Range	40 Hz - 40 kHz	Ultra High-Gloss (RAL and NCS colors)	7.500,00
		Crossover Frequency	360 Hz		
		Sensitivity	89 dB 1 W/1 m		
		Max SPL	106 dB Peak		
		Dimensions	1139 x 270 x 214 mm		
		Weight	28 kg		
		Rec. power	50 - 200 W		
		Connectors	Bi-Wiring - WBT nextgen™ Cu		
		SAM® Processing	available		


	p2	Type	Passive 2-Way Floorstanding Speaker	RAL or NCS colors (satin finish)	7.600,00
		Impedance	8 Ohms	Standard veneers (satin finish)	7.900,00
		Frequency range	30 Hz - 40 kHz	Ultra High-Gloss (RAL and NCS colors)	8.700,00
		Crossover frequency	340 Hz		
		Sensitivity	89 dB 1 W/1 m		
		Maximum SPL	112 dB Peak		
		Dimensions (HxWxD)	1139 x 270 x 214 mm		
		Weight	32 kg		
		Rec. power	50 - 200 W		
		Connectors	Bi-Wiring - WBT nextgen™ Cu		
		SAM® Processing	available		



Image	Ref.	Description	Finition	Prix/pièce
 	<p><b>z1</b></p>	Passive 2-way book shelf loudspeaker Drivers: - HF: MSW (80Hz - 40 KHz), rise time 13 µs - LF: Woofer 210mm. Special coated carbon fiber paper cone.	RAL or NCS colors (satin finish)	4.900,00
		Crossover frequency: 3 60Hz. Mundorf parts Cabinet: Closed Frequency response: 40Hz- 40 KHz Impedance: 4 Ω Sensitivity: 88 dB (1W/1m) Connectors: Bi-Wiring - WBT nextgen™ Cu	Standard veneers (satin finish)	5.200,00
		Dimensions (H x W x D): 534 x 270 x 364 mm Weight: 26 kg	Ultra High-Gloss (RAL and NCS colors)	5.900,00


Image	Ref.	Description	Finition	Prix/pièce
	<p><b>z1 stand</b></p>	Material : Aluminum anodized Dimensions : 549 (H) x 270 (top plate) x 465 (foot plate) mm Weight : 14 kg	Aluminum anodized	1.800,00


Image	Ref.	Description	Finition	Prix/pièce
	<p>w1</p>	<p>Passive 1-way on - wall speaker            Driver:            -HF: MSW (120 Hz - 40 kHz), rise time 13 μs            Cabinet: closed            Freq. response: 150 Hz - 40 kHz            Impedance: 8 Ω            Sensitivity: 90 dB (1 W/1 m)            Connectors: 1 pair binding-post            Dimensions (H x W x D): 264 x 128 x 436 mm            Weight: 8 kg</p>	<p>RAL or NCS colors (satin finish)</p> <hr/> <p>Ultra High-Gloss (RAL and NCS colors)</p>	<p>3.000,00</p> <hr/> <p>3.400,00</p>



Image	Ref.	Description	Finition	Prix/pièce		
	<p style="color: red; font-size: 24px; text-align: center;">c1</p>	<p><b>General</b></p> <p>Type Active 2-Way System            Frequency range 30 Hz – 40 kHz            Crossover frequency 330 Hz            Max. SPL 110 dB Peak            Dimensions 495 x 270 x 424 mm            Weight 30 kg</p> <p><b>Amplifiers</b></p> <p>Max. Power Output LF 250 W @ 8 Ohms Class AB            Max. Power Output HF 180 W @ 8 Ohms Class AB            Power Bandwidth HF 250 kHz (-3 dB)            Input Sensitivity 6 dBu (1.55 V) or 0 dBu            Input Impedance 10 kOhms            Input XLR-3 (balanced)</p>	<p>RAL or NCS colors (satin finish)</p> <hr/> <p>Standard veneers (satin finish)</p> <hr/> <p>Ultra High-Gloss (RAL and NCS colors)</p>	<p>8.000,00</p> <hr/> <p>8.300,00</p> <hr/> <p>8.700,00</p>		
			<p style="color: red; font-size: 24px; text-align: center;">LF Module</p> <hr/> <p style="color: red; font-size: 24px; text-align: center;">c1 stand</p>	<p>Extra passive woofer module (max. SPL +6dB)            Will be connected to c1 and switched parallel to built-in woofer no extra-amplifier required            Dimensions 264 x 270 x 343 mm            (H x W x D):            Weight: 11 kg</p> <hr/> <p>Height: 620 mm            Dimensions Foot-plate: 20 x 358 x 465 mm            Weight: 14 kg</p>	<p>RAL or NCS colors (satin finish)</p> <hr/> <p>Veneer satin finish</p> <hr/> <p>Ultra High - Gloss (RAL and NCS colors)</p>	<p>1.900,00</p> <hr/> <p>2.300,00</p> <hr/> <p>2.700,00</p>
				<p>Aluminum anodized</p>	<p>1.800,00</p>	






Image	Ref.	Description	Finition	Prix/pièce
	<p style="color: red; font-size: 24px; text-align: center;">s1</p>	<p><b>General</b>            Type Active 2-Way Floorstanding System            Frequency Range 30 Hz – 40 kHz            Crossover Frequency 330 Hz            Max SPL 110 dB Peak            Dimensions 1139 x 270 x 214 mm            Weight 48 kg</p> <p><b>Amplifiers</b>            Max. Power Output LF 250 W @ 8 Ohms Class AB            Max. Power Output HF 180 W @ 8 Ohms Class AB            Power Bandwidth HF 250 kHz (-3 dB)            Input Sensitivity 6 dBu (1.55 V) or 0 dBu            Input Impedance 10 kOhms            Input XLR-3 (balanced)</p>	RAL or NCS colors (satin finish)	9.800,00
			veneers (satin finish)	10.100,00
			Ultra High-Gloss (RAL and NCS colors)	10.900,00

Image	Ref.	Description	Finition	Prix/pièce
	<p><b>Manger® Hologram</b></p>	<p><b>Invented and patented sound guide</b> Shaped high-attenuation special thermoplastic, fixed with high-attenuation PU plastic mounting points: acoustically decoupling double-sided adhesive pads.</p>		<p>450,00</p>
	<p><b>Manger® cone feet</b></p>	<p><b>High damping POM plastic cone feet</b> ( H 14mm x ø18mm) with M8 thread 1 set = 8 pcs.  (comes standard with all floor standing speaker models)</p>	<p>black</p>	<p>128,00</p>
	<p><b>Manger® CD</b></p>	<p><b>Music Sampler - 15 tracks, 16 bit/44.1kHz</b>  <i>"Please give my compliments to the person who compiled your demonstration CD, it's the best in business" - Flemming E. Rasmussen, Gryphon Audio</i></p>		<p>22,00</p>
	<p><b>Manger® Double LP</b></p>	<p><b>Music Sampler - 15 tracks, 2 LPs, 180 grams - manufactured with virgin vinyl</b>  <i>"These records can tell a lot about the quality of any analogue playback chain. Thank you to Manger for providing such a useful tool!" - Hartmut Quaschik - <a href="http://www.tnt-audio.com">www.tnt-audio.com</a></i></p>		<p>58,00</p>